

River Rock



RIVER ROCK – SOUTHSIDE 1 1/2" X 3/4" ROUND ROCK

Southside 1 1/2" x 3/4" Round Rock is well suited for use in septic leach fields, backfill for retaining walls, and drainage blankets. In special portland cement concrete mixes it can be used as a coarse aggregate ingredient. In landscaping applications it is used as a decorative aggregate and as an ingredient of the streambed gravel blend. This material has a tendency to be light tan or brownish color when dry.

Located along the Tres Pinos Creek, Southside Sand and Gravel is about a mile west of Tres Pinos, California. (The quarry entrance is off Airline Highway.) The deposit was created by the combined ancestral flow of the San Benito River & Tres Pinos Creek. The site is characterized by extensive deposits of sand and gravel, comprised of granite, dolomite, limestone, sandstone and gneiss materials.



SOUTHSIDE 1 1/2" X 3/4" ROUND ROCK

SIEVE ANALYSIS

INCHES	MM / UM	SOUTHSIDE GRADING	ASTM C-33, AREA BALLAST SPECIFICATION, ASTM D-448
2"	50 mm	100	100
1 1/2"	37.5 mm	95	90 – 100
1"	25 mm	37	20 – 55
3/4"	19 mm	6	0 – 15
3/8"	9.5 mm	1	0 – 5

ASTM SPECIFICATIONS & PHYSICAL PROPERTIES

Specific Gravity	2.5
------------------	-----